



VAPORFLEX™ Secondary Seal



The HMT VAPORFLEX™ Secondary Seal is the first internal secondary seal to combine flexibility, low profile, light weight, abrasion resistance, 100% MTBE and ethanol compatible materials, and fifteen plus years life cycle into a competitively priced secondary seal.

The VAPORFLEX Secondary Seal for internal floating roofs, was developed specifically to resist the many products and additives normally stored in floating roof tanks. It's PETROFLEX™ (PTFE) wiper/vapor barrier fabric construction makes the VAPORFLEX Secondary Seal resistant to all stored products including benzene, methanol, toluene, naphtha, ETBE, TAME, ethanol, and MTBE.

The VAPORFLEX Secondary Seal has unsurpassed gap sealing ability combined with the longest service life of any secondary seal for internal floating roofs. Engineered for rapid field installation, the VAPORFLEX Secondary Seal can be installed on both aluminum and steel roofs.

Contact your local HMT representative to discuss the full suite of products and services that will satisfy all your AST needs.

HMT'S VAPORFLEX™ Secondary Seal Unique Design Features Include:

- Low profile
- Resistant to all products normally stored in floating roof tanks
- Longest service life of any secondary seal for internal floating roofs
- Petroflex™ PTFE (Teflon®) wiper/vapor barrier fabric construction
- Stainless steel metal parts
- Excellent gap sealing ability
- Rapid installation with both aluminum and steel internal floating roofs
- Light weight
- Abrasion resistant



HMT Inc.
24 Waterway Avenue, Suite 400
The Woodlands, Texas 77380
Ph: +1.281.681.7000
Fax: +1.281.419.7689

Locations worldwide to service
all your AST needs.

Visit us at www.hmttank.com